

SAFETY DATA SHEET **SDS No. 403A**

Revision Date: December 5, 2023 Version 3.0

GHS Compliant

Section 1 - Identification of the substance/mixture and of the company

1.1 **Product Identifier**

> Trade Name: Part A: Smooth-Cast ONYX

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use: Polyurethane Elastomer

Restrictions on Use: None known

1.3 Details of the supplier of the safety data sheet:

> Company: Smooth-On, Inc.,

> > 5600 Lower Macungie Rd., Macungie, PA 18062

Telephone: Phone (610) 252-5800 FAX (610) 252-6200

E-mail address: Visit our website at www.smooth-on.com or email

www.sds@smooth-on.com

Name, address, and telephone number of the supplier: Refer to manufacture

1.4 **Emergency Contact:** Chem-Tel Domestic: 800-255-3924 International: 813-248-0585

Section 2 – Hazard(s) Identification

2.1 Classification of the substance or mixture:

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

H315 Skin corrosion/irritation – Category 2

H317 Skin sensitization - Category 1

H320 Eye Damage/irritation - Category 2B

H332 Acute toxicity, inhalation – Category 4

H334 Respiratory Sensitization - Category 1

H335 Specific target organ toxicity – single exposure – Category 3 (respiratory)

H351 Carcinogenicity – Category 2

H373 Specific Target Organ Toxicity, repeated exposure Category 2 (respiratory)

2.2 GHS Label elements, including precautionary statements

Pictogram(s):

Signal word: Danger

Health Hazards

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H320 Causes eve irritation.

H332	Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs (Olfactory organs) through prolonged or

repeated exposure (inhalation).

General Precautions

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Prevention Precautions

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

Response Precautions

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308 + P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P332 + P313 IF SKIN irritation occurs: Get medical advice/attention.

P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.

P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage Precautions

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal Precautions

P501 Dispose of contents/container according to local, state and federal laws.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS – none known

Section 3 - Composition / Information on Ingredients

3.1 Substances/Mixtures

The following ingredients are hazardous according to Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015):

Chemical name	CAS-No.	Concentration
4,4' Methylene bis(phenylisocyanate) (MDI)	101-68-8	15 – 35
Benzene, 1,1'-methylenebis[4-isocyanato-], homopolymer	25686-28-6	5 – 10
Methylenediphenyl diisocyanate	26447-40-5	< 1.5

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact

Flush eyes with plenty of water occasionally lifting the upper and lower eyelids. Check and remove any contact lenses if safe to do so. Continue to rinse for at least 15 minutes. If irritation develops, seek medical attention.

Skin Contact

In case of skin contact, wash thoroughly with soap and water. Continue to rinse for at least 15 minutes. Chemical burns must be treated promptly by a physician.

Ingestion

Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. if vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

4.2 Most important symptoms and effects, both acute and delayed

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

4.3 Indication of any immediate medical attention and specific treatment needed, if necessary.

Section 5 - Fire-Fighting Measures

5.1 Extinguishing Media

Water Fog, Dry Chemical, and Carbon Dioxide Foam

5.2 Special hazards arising from the substance or mixture

In a fire or if heated, a pressure increase will occur, and the container may burst.

5.3 Advice for firefighters

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full-face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Only properly protected personnel should remain in the spill area; dike and contain spill. Stop or reduce discharge if it can be done safely.

6.2 Environmental precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains or unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Put on appropriate protective gear including NIOSH/MSHA approved self-contained breathing apparatus, rubber boots and heavy rubber gloves. Dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely. Follow applicable OSHA regulations (29 CFR 1910.120) for disposal.

6.4 Reference to other sections

See Section 3 for list of Hazardous Ingredients; Sections 8 for Exposure Controls; and Section 13 for Disposal.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Use good general housekeeping procedures. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices.

7.2 Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet local standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

7.3 Specific end use(s)

These precautions are for room temperature handling. Other uses including elevated temperatures or aerosol/spray applications may require added precautions.

Section 8 - Exposure Controls / Personal Protection

8.1 Control parameters Components with workplace control parameters

Component	CAS-No.	Value	Control Parameters	Basis
4,4' Methylene bis(phenylisocyanate) (MDI)	101-68-8	0.005 ppm	TWA	ACGIH
		0.2 mg/m3 0.02 ppm	С	OSHA Z-1
		0.05 mg/m3 0.005 ppm	TWA	NIOSH REL

8.2 Exposure controls Respiratory Protection

Respiratory protection is not normally required when using this product with adequate local exhaust ventilation. Where risk assessment shows air-purifying respirators are appropriate, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with appropriate filter cartridges as a backup to engineering controls.

Hand Protection

Wear any liquid-tight gloves such as butyl rubber, neoprene or PVC.

Eye Protection

Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Other Protective Clothing/Equipment

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

Comments

Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

Section 9 - Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Amber liquid	Vapor pressure:	< 0.00016 mmHg (68 °F)
Odor:	Musty odor	Vapor density (Air=1):	>1.0
pH:	No data	Evaporation rate:	No data
Flash Point:	>300 °F	Solubility in water:	Insoluble
		Specific Gravity	
Melting / freezing point:	37°F	(H2O=1, at 4 °C):	No data
Low / high boiling point:	No data	Relative density:	No data
Upper flammability limits:	No data	Decomposition temperature:	No data
Lower flammability limits:	No data	Viscosity:	30 – 100 cPs

Section 10 - Stability and Reactivity

10.1 Reactivity

No hazardous reactions if stored and handled as prescribed/indicated., No corrosive effect on metal. Not fire propagating.

10.2 Chemical stability

These products are stable at room temperature in closed containers under normal storage and handling conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerization cannot occur

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Strong bases and acids

10.6 Hazardous decomposition products

Thermal oxidative decomposition can produce carbon oxides, gasses/vapors, and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information

11.1 Information on toxicological effects Acute Toxicity

Calculated based on MDI LD50 oral (rat): > 6,250 mg/kg

LC50 inhalation (rat): >6.25 mg/l (OECD Guideline 403)

LD50 dermal (rabbit): > 29,400 mg/kg

Chronic Exposure

NOAEL: 0.6 mg/m3; LOAEL: 3.1 mg/m3 (based on MDI)

Skin Corrosion/Irritation

Draize test (rabbit): irritating (based on MDI).

Serious Eye Damage/Irritation

Draize test (rabbit): irritating (based on MDI).

Respiratory/Skin Sensitization

Buehler test (guinea pig): sensitizing

Mouse Local Lymph Node Assay (LLNA): sensitizing, can cause skin sensitization. Studies in animals suggest that dermal exposure may lead to pulmonary sensitization. However, the relevance of this result for humans is unclear.

Germ Cell Mutagenicity

No data available

Carcinogenicity

A carcinogenic potential cannot be excluded after prolonged exposure to severely irritating concentrations. These effects are not relevant to humans at occupational levels of exposure. OECD Guideline 453 rat inhalation 0, 0.2, 1, 6 mg/m3 result: lung tumors.

Reproductive Toxicity

Repeated inhalation uptake of the substance did not cause damage to the reproductive organs. Assessment of teratogenicity showed that the substance did not cause malformations in animal studies, however toxicity to development was observed at high doses that were toxic to the parental animals.

Development:

OECD Guideline 414 rat inhalation 0, 1, 4, 12 mg/m3

NOAEL Mat: 4 mg/m3

NOAEL Teratogenic: 4 mg/m3

Specific Target Organ Toxicity - Single Exposure

No data available

Specific Target Organ Toxicity - Repeated Exposure

No data available

Aspiration Hazard

No data available

Potential Health Effects - Miscellaneous

No data available

Section 12 - Ecological Information

12.1 Toxicity

LC0 (96 h): > 1,000 mg/l, Brachydanio rerio (OECD Guideline 203, static) EC50 (24 h): > 1,000 mg/l, Daphnia magna (OECD Guideline 202, part 1, static) EC0 (72 h): 1,640 mg/l (growth rate), Scenedesmus subspicatus, (OECD Guideline 201, static

12.2 Persistence and Degradability

Poorly biodegradable (0% BOD OECD Guideline 302 C). This product is unstable in water. The elimination data also refer to products of hydrolysis.

12.3 Bioaccumulative Potential

Significant accumulation in organisms is not to be expected. Bioconcentration factor 200 (28 d) Cyprinus carpio (OECD Guideline 305 E)

12.4 Mobility in Soil

Adsorption to solid soil phase is not expected.

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other Adverse Effects

The substance will not evaporate into the atmosphere from the water surface.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification

Container disposal

Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Do not reuse empty containers.

Section 14 - Transport Information

Not regulated by DOT / IMDG / IATA

Section 15 - Regulatory Information

15.1 Safety health and environmental regulations/legislation specific for the substance or mixture:

REACH: Regulation (EC) No 1907/2006 of The European Parliament and of The Council of December 2006 (including amendments and corrigenda as of June 2023)

This product complies with REACH or is not subject to regulation under REACH. The product does not contain an ingredient listed on either the Candidate List or Authorization List for Substances of Very High Concern (SVHC).

In the United States (EPA Regulations) TSCA Inventory Status (40 CFR710)

All components of this formulation are listed in the TSCA Inventory. No component of this formulation has been determined to be subject to manufacturing or use restrictions under the Significant New Use Rules (SNURs).

CERCLA Hazardous Substance List (40 CFR 302.4)

None known.

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA))

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and community Right-to-Know Act of 1986) Sections 311 and 312 Immediate (Acute), Delayed (Chronic)

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

Component	CAS#	Concentration (%wt)
4,4' Methylene bis(phenylisocyanate) (MDI)	101-68-8	15 – 35

California Proposition 65

This product does not intentionally contain any chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

15.2 Chemical safety assessment

No chemical safety assessment has been carried out for this substance/mixture by the supplier.

16 - Other Information



Revision Date: December 5, 2023 Version 3.0

Abbreviations and acronyms

ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; NFPA-National Fire Protection Association; OEL-OccupationalExposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer

The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.



SAFETY DATA SHEET SDS No. 403B

Revision Date: December 5, 2023 Version 3.0

GHS Compliant

Section 1 - Identification of the substance/mixture and of the company

1.1 Product Identifier

Trade Name: Part B: Smooth-Cast ONYX Fast

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use: Polyurethane Elastomer

Restrictions on Use: None known

1.3 Details of the supplier of the safety data sheet:

Company: Smooth-On, Inc.,

5600 Lower Macungie Rd., Macungie, PA 18062

Telephone: Phone (610) 252-5800 FAX (610) 252-6200

E-mail address: Visit our website at www.smooth-on.com or email

www.sds@smooth-on.com

Name, address, and telephone number of the supplier: Refer to manufacture

1.4 Emergency Contact: Chem-Tel Domestic: 800-255-3924 International: 813-248-0585

Section 2 - Hazard(s) Identification

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) and Regulation (EC) No 1272/2008 and subsequent amendments.

2.2 GHS Label elements, including precautionary statements

Pictogram(s): none Signal word: none

General Precautions:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS – none

This product contains a chemical known to be hazardous according to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). (See also Section 15).

Section 3 - Composition / Information on Ingredients

3.1 Substances

No ingredients are hazardous according to Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015):

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact

Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact

In case of skin contact, wash thoroughly with soap and water.

Ingestion

Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and specific treatment needed.

None known.

Section 5 - Fire-Fighting Measures

5.1 Extinguishing Media

Water Fog, Dry Chemical, and Carbon Dioxide Foam

5.2 Special hazards arising from the substance or mixture

None known.

5.3 Advice for firefighters

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full-face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Only properly protected personnel should remain in the spill area; dike and contain spill. Stop or reduce discharge if it can be done safely.

6.2 Environmental precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains or unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Put on appropriate protective gear including NIOSH/MSHA approved self-contained breathing apparatus, rubber boots and heavy rubber gloves. Dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely. Follow applicable OSHA regulations (29 CFR 1910.120) for disposal.

6.4 Reference to other sections

See Section 3 for list of Hazardous Ingredients; Sections 8 for Exposure Controls; and Section 13 for Disposal.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Use good general housekeeping procedures. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices.

7.2 Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet local standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

7.3 Specific end use(s)

These precautions are for room temperature handling. Other uses including elevated temperatures or aerosol/spray applications may require added precautions.

Section 8 - Exposure Controls / Personal Protection

8.1 Control parameters

None defined

8.2 Exposure controls

Respiratory Protection

Respiratory protection is not normally required when using this product with adequate local exhaust ventilation. Where risk assessment shows air-purifying respirators are appropriate, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with appropriate filter cartridges as a backup to engineering controls.

Hand Protection

Wear any liquid-tight gloves such as butyl rubber, neoprene or PVC.

Eye Protection

Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Other Protective Clothing/Equipment

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

Comments

Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

Section 9 - Physical and Chemical Properties

9.1 Information on basic physical and chemical properties:

Appearance:	Translucent viscous liquid	Vapor pressure:	No data
Odor:	Mild to sweet odor	Vapor density (Air=1):	> 1
pH:	No data	Evaporation rate:	No data
Flash Point:	>300 °F	Solubility in water:	Insoluble
		Specific Gravity	
Melting / freezing point:	No data	(H2O=1, at 4 °C):	1.07
Low / high boiling point:	No data	Relative density:	No data
Upper flammability limits:	No data	Decomposition temperature:	No data
Lower flammability limits:	No data	Viscosity:	20K-30K cPs

Section 10 - Stability and Reactivity

10.1 Reactivity

No hazardous reactions if stored and handled as prescribed/indicated., No corrosive effect on metal. Not fire propagating.

10.2 Chemical stability

These products are stable at room temperature in closed containers under normal storage and handling conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerization cannot occur

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Strong bases and acids

10.6 Hazardous decomposition products

Thermal oxidative decomposition can produce carbon oxides, gasses/vapors, and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity

No data available

Skin Corrosion/Irritation

No data available

Serious Eye Damage/Irritation

No data available

Respiratory/Skin Sensitization

No data available

Germ Cell Mutagenicity

No data available

Carcinogenicity

No component of these products present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC, ACGIH or NTP.

Reproductive Toxicity

No data available

Specific Target Organ Toxicity - Single Exposure

No data available

Specific Target Organ Toxicity – Repeated Exposure

No data available

Aspiration Hazard

No data available

Potential Health Effects - Miscellaneous

No data available

Section 12 - Ecological Information

12.1 Toxicity

No data available

12.2 Persistence and Degradability

No data available

12.3 Bioaccumulative Potential

No data available

12.4 Mobility in Soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other Adverse Effects

No data available

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification

Container disposal

Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Do not reuse empty containers.

Section 14 - Transport Information

Not regulated by DOT / IMDG / IATA

Section 15 - Regulatory Information

15.1 Safety health and environmental regulations/legislation specific for the substance or mixture:

REACH: Regulation (EC) No 1907/2006 of The European Parliament and of The Council of December 2006 (including amendments and corrigenda as of June 2023)

This product complies with REACH or is not subject to regulation under REACH. The product does not contain an ingredient listed on either the Candidate List or Authorization List for Substances of Very High Concern (SVHC).

In the United States (EPA Regulations) TSCA Inventory Status (40 CFR710)

All components of this formulation are listed in the TSCA Inventory. No component of this formulation has been determined to be subject to manufacturing or use restrictions under the Significant New Use Rules (SNURs).

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA))

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and community Right-to-Know Act of 1986) Sections 311 and 312

None

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

KEEP OUT OF REACH OF CHILDREN



WARNING: This product can expose you to chemicals including Di-isodecyl phthalate (DIDP) (CAS 68515-49-1), Carbon Black (CAS 1333-86-4), which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

15.2 Chemical safety assessment

No chemical safety assessment has been carried out for this substance/mixture by the supplier.

16 - Other Information





Revision Date: December 5, 2023 Version 3.0

Abbreviations and acronyms

ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals: HMIS-Hazardous Material Information Service: IATA-International Air Transport Association: IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; LEL-Lower Explosion Level; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor: PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit: TCEQ-Texas Commission on Environmental Quality: TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; UEL-Upper Explosion Level; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer

The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.